

Pro 4 DX



The Pro 4 DX makes serger sewing easy! Incorporating the differential feed system of two feed dogs, puckered edges on woven fabrics and stretched edges on knits are virtually eliminated. The rolled hem conversion feature eliminates the need to change the needle plate, foot, or tension setting for rolled hemming. Restructured lower looper guides allow easy access. The included threading card and color-coded guides are easy to follow for 2, 3, or 4 thread serging.

FEATURES

- 2 and 3 / 4 thread overlock
- Regular type needle
- 1 - 5mm seam length
- 3.5mm (regular); 5.7mm (wide); 2.0mm (narrow) seam width
- 0.5 - 2.25 differential feed ration
- Front and back needle guard
- Color coded thread guides
- Snap-on presser feet
- Electronic speed control
- Easy to follow upper thread guide
- Dual feed dogs and differential feed
- Adjustable cutting width
- Easily retractable upper knife
- Easy to reach lower looper guides
- Quick change rolled hem
- Solid metal base plate

SPECIFICATIONS

Skeleton Body Construction

Lay-in Tension Dial

2, 3 and 4 Thread Convertible

Maximum Speed: 1,300 spm

Incorporated Tension Release Device

Incorporated Rolled Hem Changed Over Device

Adjustable Foot Pressure (Adjusting Screw)

Snap-on Presser Foot

Feed Adjustment: Dial on Belt Cover (with Window)

Differential Feed Adjustment: Dial on Belt Cover (with Window)

Dial Cutting Width Adjustment

Aligned Spool Pin Spool Stand

Carrying Handle: Part of Machine Body

Thread Cutter (Underneath the Face Plate)

Length of Feet: 1 to 5 mm

Differential Feed Ratio: 0.5 to 2.25

Cutting Width: 3.1 - 7.3 mm

Waste Chip Box

Accessory Box

Foot Controller